


**MOORING PLAN JETTY 3
<10,000 SDWT VESSELS**

BOLLARD	BOLLARD CAPACITY	TYPE LINE
2-B07	550 kN	BOWLINE
2-B08	550 kN	BOWLINE
3-B01	550 kN	BOWLINE
3-B02	550 kN	BOWLINE
3-B03	550 kN	STERNLINE
3-B04	550 kN	STERNLINE
3-B10-B13	600 kN	SPRINGLINE
3-B14-B19	800 kN	SPRINGLINE
3-B20-25	600 kN	SPRINGLINE
3-B26-19	600 kN	SPRINGLINE
4-B01	550 kN	STERNLINE
4-B02	550 kN	STERNLINE

NOTES:

- NO MIXED MOORING
- NO MORE THAN 2 LINES PER BOLLARD
- MINIMUM MOORING REQUIREMENTS:
 - SHIPS < 10,000 DWT: 2 HEAD- AND STERNLINES, 2 SPRINGLINES FWD AND AFT
 - SHIPS < 25,000 DWT: 3 HEAD- AND STERNLINES, 2 SPRINGLINES FWD AND AFT
 - SHIPS > 25,000 DWT: 4 HEAD- AND STERNLINES, 2 SPRINGLINES FWD AND AFT



REV	DATE	DESCRIPTION	BUREAU	AFD

B 02-11-21 UPDATE VERWERKT DMS 748
A 02-05-12 FIRST ISSUE DMS 73131

REV	DATE	DESCRIPTION	BY	CHKD
01				

**MOORING PLAN
T.B.V SCHEPEN TOT 100m LENGTE
STEIGER 3**

reference	drawing	R-0415000	SHEET 1	of 1	REVISE
	drawing				
	drawing				

R0809034 B

Shell Nederland Raff./Chemie b.v.
 R-0415000
 R-0415000
 R-0415000

